






The Pride of Top Quality
FOOT MASTER®

高荷重脚轮




轮子选项导航：高荷重脚轮

图片	区分	轮轴说明	轮子代码	轮子外径 mm	轮宽 mm	轴径 mm	轴厚 mm	允许载重 Kg	轴承规格
	NYD	- 尼龙66(Shore D70) - 球轴承 2个	NYD-100-48	100	48	20	48	600	6204 ZZ
	MUD	- 浇注型聚氨酯(Shore A95) - 铝合金轮毂 - 球轴承 2个	MUD-100-67	100	67	25	73	650	6005 ZZ
			MUD-125-64	125	64	25	73	750	6005 ZZ
			MUD-150-64	150	64	25	73	800	6205 ZZ
			MUD-200-64	200	64	25	73	850	6205 ZZ
	MCD	- MC尼龙(Shore D80) - 球轴承 2个	MCD-75-40	75	40	25	40	850	6005 ZZ
			MCD-80-48	80	48	20	48	800	6204 ZZ
			MCD-100-40	100	40	25	40	1,000	6005 ZZ
			MCD-100-48	100	48	20	48	900	6204 ZZ
			MCD-100-67	100	67	25	73	800	6005 ZZ
			MCD-125-40	125	40	25	40	1,100	6005 ZZ
			MCD-125-64	125	64	25	73	900	6005 ZZ
			MCD-125-68	125	68	25	70	1,500	6205 ZZ
			MCD-150-64	150	64	25	73	1,000	6205 ZZ
			MCD-150-68	150	68	30	70	2,200	6206 ZZ
			MCD-200-64	200	64	25	73	1,100	6205 ZZ
			MCD-200-68	200	68	30	70	2,500	6206 ZZ
			MCD-250-64	250	64	25	73	1,300	6205 ZZ
			MCD-250-70	250	70	30	70	2,700	6206 ZZ
MCD-250-78	250	78	35	78	3,500	6210 ZZ			
MCD-300-78	300	78	35	78	4,000	6210 ZZ			
	MCQ	- MC尼龙(Shore D80) - 球轴承 4个	MCQ-200-100	200	100	50	100	6,000	6210 ZZ
			MCQ-250-100	250	100	50	100	7,000	6210 ZZ
			MCQ-300-100	300	100	50	100	8,000	6210 ZZ
	HUD	- 浇注型聚氨酯(Shore A95) - 碳钢轮毂 - 球轴承 2个	HUD-100-29	100	29	15	27	200	6202 ZZ
			HUD-110-29	110	29	15	27	200	6202 ZZ
			HUD-150-40	150	40	17	40	400	6203 ZZ
			HUD-200-65	200	65	25	65	1,250	6205 ZZ
			HUD-250-78	250	78	35	78	2,200	6210 ZZ
	HUD	- 浇注型聚氨酯(Shore D70) - 碳钢轮毂 - 球轴承 2个	HUD-80-48	80	48	20	48	500	6204 ZZ
			HUD-100-48	100	48	20	48	600	6204 ZZ
	HUQ	- 浇注型聚氨酯(Shore A95) - 碳钢轮毂 - 球轴承 4个	HUQ-100-50	100	50	15	62	400	6202 ZZ
	HUD	- 浇注型聚氨酯(Shore D70) - 铝合金轮毂 - 球轴承 2个	HUD-75-40	75	40	25	40	400	6005 ZZ
			HUD-100-40	100	40	25	40	550	6005 ZZ
			HUD-125-40	125	40	25	40	700	6005 ZZ
	HUD	- 浇注型聚氨酯(Shore A95) - 铝合金轮毂 - 球轴承 2个	HUD-125-70	125	70	25	70	1,100	6205 ZZ
			HUD-150-68	150	68	30	70	1,500	6206 ZZ
			HUD-200-68	200	68	30	70	2,000	6206 ZZ
	HUQ	- 浇注型聚氨酯(Shore A95) - 铝合金轮毂 - 球轴承 4个	HUD-250-64	250	64	30	70	2,300	6206 ZZ
			HUQ-200-100	200	100	50	100	2,500	6210 ZZ
			HUQ-250-100	250	100	50	100	2,900	6210 ZZ
			HUQ-300-100	300	100	50	100	3,300	6210 ZZ

高荷重脚轮

GF series

kg 650~1,300kg RoHS °C -10~90°C



产品说明: 锻造脚轮座, 使用强化热处理的双重钢珠槽旋转结构, 坚固的焊接支架, 钢制踏板刹车系统, 螺栓式轮轴紧固构造
表面处理: 镀锌

* 4轮允许承载 = 单轮运行承载 × 3

万向型	固定型	万向 刹车型	固定 刹车型	轮子 种类	mm	mm	Kg	mm	mm	mm	mm	mm
GF-100-ASF	GF-100-ARF	GF-100-BSF	GF-100-BRF	MUD	100	67	650	145	37	159x114	134x86 126x62	13
GF-125-ASF	GF-125-ARF	GF-125-BSF	GF-125-BRF		125	64	750	167	44			
GF-150-ASF	GF-150-ARF	GF-150-BSF	GF-150-BRF		150	64	800	190	52			
GF-200-ASF	GF-200-ARF	GF-200-BSF	GF-200-BRF		200	64	850	257	57			
GF-250-ASF	GF-250-ARF	GF-250-BSF	GF-250-BRF		250	64	1,200	300	61			
GF-100-ASF	GF-100-ARF	GF-100-BSF	GF-100-BRF	MCD	100	67	800	145	37	159x114	134x86 126x62	13
GF-125-ASF	GF-125-ARF	GF-125-BSF	GF-125-BRF		125	64	900	167	44			
GF-150-ASF	GF-150-ARF	GF-150-BSF	GF-150-BRF		150	64	1,000	190	52			
GF-200-ASF	GF-200-ARF	GF-200-BSF	GF-200-BRF		200	64	1,100	257	57			
GF-250-ASF	GF-250-ARF	GF-250-BSF	GF-250-BRF		250	64	1,300	300	61			

选项


产品编号	MUD	MCD	-FRN			
产品特征	浇注型聚氨酯(A95)	MC尼龙(D80)	刹车方向			
适用型号	100 ~ 250	100 ~ 250	150 ~ 250			

高荷重脚轮


GXT series



kg 500~2,700kg **RoHS** **°C -10~90°C**



GXT(80~100)



GXT(125~250)

产品说明: 锻造脚轮座, 使用2列推力球轴承优化旋高荷重转性的结构(125~250系列: 推力球轴承+圆锥滚子轴承), 坚固的焊接支架, 手动刹车系统, 使用特殊形态的轮轴强化旋转性
表面处理: 粉末喷涂, 镀锌

* 4轮允许承载 = 单轮运行承载 × 3

万向型	固定型	万向刹车型	轮子种类	 mm	 mm	 Kg	 mm	 mm	 mm	 mm	 mm
GXT-80-ASF	GXT-80-ARF	GXT-80-BSF	HUD	80	48	500	120	40	100x85	80x60	9
GXT-100-ASF	GXT-100-ARF	GXT-100-BSF		100	48	600	140	40			
GXT-125-ASF	GXT-125-ARF	GXT-125-BSF		125	70	1,100	170	77.5			
GXT-150-ASF	GXT-150-ARF	GXT-150-BSF		150	68	1,500	224	48	175x140	148x111 132x99	14
GXT-200-ASF	GXT-200-ARF	GXT-200-BSF		200	68	2,000	275	60			
GXT-250-ASF	GXT-250-ARF	GXT-250-BSF		250	64	2,300	310	75			
GXT-80-ASF	GXT-80-ARF	GXT-80-BSF	MCD	80	48	800	120	40	100x85	80x60	9
GXT-100-ASF	GXT-100-ARF	GXT-100-BSF		100	48	900	140	40			
GXT-125-ASF	GXT-125-ARF	GXT-125-BSF		125	70	1,500	170	77.5			
GXT-150-ASF	GXT-150-ARF	GXT-150-BSF		150	70	2,200	200	80	175x140	148x111 132x99	14
GXT-200-ASF	GXT-200-ARF	GXT-200-BSF		200	70	2,500	260	75			
GXT-250-ASF	GXT-250-ARF	GXT-250-BSF		250	70	2,700	310	75			
GXT-100-ASF	GXT-100-ARF	GXT-100-BSF	NYD	100	48	900	140	40	100x85	80x60	9

选项

						
产品编号	HUD	HUD	MCD	NYD		
产品特征	浇注型聚氨酯(D70)	浇注型聚氨酯(A95)	MC尼龙(D80)	尼龙66(D70)		
适用型号	80 ~ 100	125 ~ 250	80 ~ 250	100		

高荷重脚轮


GXT series



500~600kg



-10~90°C



产品说明: 锻造脚轮座, 使用2列推力球轴承优化旋高荷重转性的结构, 坚固的焊接支架, 手动刹车系统, 使用特殊形态的轮轴强化旋转性,

表面处理: 粉末喷涂, 镀锌

* 4轮允许承载 = 单轮运行承载 × 3

万向型	万向刹车型	轮子种类	mm	mm	Kg	mm	mm	mm	mm	mm
GXT-80-ASS	GXT-80-BSS	HUD	80	48	500	120	40	TM32-4 or M36x4.0P	115+15	20
GXT-100-ASS	GXT-100-BSS		100	48	600	140	40			
GXT-80-ASS	GXT-80-BSS	MCD	80	48	500	120	40	TM32-4 or M36x4.0P	115+15	20
GXT-100-ASS	GXT-100-BSS		100	48	600	140	40			
GXT-100-ASS	GXT-100-BSS	NYD	100	48	600	140	40	TM32-4 or M36x4.0P	115+15	20

选项


产品编号	HUD	MCD	NYD			
产品特征	浇注型聚氨酯(D70)	MC尼龙(D80)	尼龙66(D70)			
适用型号	80 ~ 100	80 ~ 100	100			

高荷重脚轮

GXTT series











kg 800~2,300kg **RoHS** **°C** -10~90°C





产品说明: 锻造脚轮座, 使用推力球轴承+圆锥滚子轴承优化旋高荷重转性的结构, 坚固的焊接支架, 手动刹车系统, 螺栓式轮轴紧固构造

表面处理: 粉末喷涂, 镀锌

* 4轮允许承载 = 单轮运行承载 × 3

万向型	固定型	万向 刹车型	固定 刹车型	轮子 种类	 mm	 mm	 Kg	 mm	 mm	 mm	 mm	 mm
GXTT-75-ASF	GXTT-75-ARF	GXTT-75-BSF	GXTT-75-BRF	HUD	75	40x2	800	125	45	[SF]	105x80	13
GXTT-100-ASF	GXTT-100-ARF	GXTT-100-BSF	GXTT-100-BRF		100	40x2	1,100	150	50	140x110 [RF]		
GXTT-125-ASF	GXTT-125-ARF	GXTT-125-BSF	GXTT-125-BRF		125	40x2	1,400	175	55	140x117		
GXTT-75-ASF	GXTT-75-ARF	GXTT-75-BSF	GXTT-75-BRF	MCD	75	40x2	1,700	125	45	[SF]	105x80	13
GXTT-100-ASF	GXTT-100-ARF	GXTT-100-BSF	GXTT-100-BRF		100	40x2	2,000	150	50	140x110 [RF]		
GXTT-125-ASF	GXTT-125-ARF	GXTT-125-BSF	GXTT-125-BRF		125	40x2	2,300	175	55	140x117		


选项

						
产品编号	HUD	MCD				
产品特征	浇注型聚氨酯(D70)	MC尼龙(D80)				
适用型号	75 ~ 125	75 ~ 125				


高荷重脚轮

GXTD series

kg 400~8,000kg RoHS °C -10~90°C



GXTD(100~200)



GXTD(250~300)

产品说明: 锻造脚轮座, 使用2列推力球轴承优化旋高荷重转性的结构, (250/300系列: 推力球轴承+圆锥滚子轴承), 使用油脂嘴, 坚固的焊接支架, 螺栓式轮轴紧固构造
表面处理: 粉末喷涂, 镀锌

* 4轮允许承载 = 单轮运行承载 × 3

万向型	固定型	轮子种类	mm	mm	Kg	mm	mm	mm	mm	mm
GXTD-100-ASF	GXTD-100-ARF	HUD	100	29x2	400	156	35	140x112	110x75 105x80	11
GXTD-110-ASF	GXTD-110-ARF		110	29x2	400	156	30	112x112	88x88	9
GXTD-150-ASF	GXTD-150-ARF		150	40x2	800	200	35	145x130	115x100	11
GXTD-200-ASF	GXTD-200-ARF		200	65x2	2,500	265	50	210x210	170x170	17
GXTD-250-ASF	GXTD-250-ARF		250	78x2	4,500	330	70	255x215	210x160	18
GXTD-300-ASF	GXTD-300-ARF		300	78x2	5,200	390	80			
GXTD-250-ASF	GXTD-250-ARF	MCD	250	78x2	7,000	330	70	255x215	210x160	18
GXTD-300-ASF	GXTD-300-ARF		300	78x2	8,000	390	80			


选项

产品编号	HUD	MCD				
产品特征	浇注型聚氨酯(A95)	MC尼龙(D80)				
适用型号	100 ~ 300	250 ~ 300				

高荷重脚轮

UGXT series

 2,500~8,000kg  RoHS  -10~90°C





产品说明: 锻造脚轮座, 用推力球轴承+圆锥滚子轴承优化旋高荷重转性的结构, 使用油脂嘴, 坚固的焊接支架, 手动刹车系统, 使用特殊形态的轮轴强化旋转性
表面处理: 粉末喷涂, 镀锌

* 4轮允许承载 = 单轮运行承载 × 3

万向型	固定型	万向 刹车型	轮子 种类	 mm	 mm	 Kg	 mm	 mm	 mm	 mm	 mm
UGXT-200-ASF	UGXT-200-ARF	UGXT-200-BSF	HUQ	200	100	2,500	280	75	255x215	210x160	18
UGXT-250-ASF	UGXT-250-ARF	UGXT-250-BSF		250	100	2,900	330	80			
UGXT-300-ASF	UGXT-300-ARF	UGXT-300-BSF		300	100	3,300	380	90			
UGXT-200-ASF	UGXT-200-ARF	UGXT-200-BSF	MCQ	200	100	6,000	280	75	255x215	210x160	18
UGXT-250-ASF	UGXT-250-ARF	UGXT-250-BSF		250	100	7,000	330	80			
UGXT-300-ASF	UGXT-300-ARF	UGXT-300-BSF		300	100	8,000	380	90			

选项

						
产品编号	HUQ	MCQ				
产品特征	浇注型聚氨酯(A95)	MC尼龙(D80)				
适用型号	200 ~ 300	200 ~ 300				